

## PONB-48 Pure Optical No Barrier

The Pure Optical No Barrier turnstile utilizes unique Beam Scan optical detection solution. With its smooth lines making this architecturally pleasing in any lobby, the standard finishes of stainless steel pedestals and Corian tops complement any setting.

The 48 inch can be upgraded to The Optical Swing Arm Barrier (OSAB).



**Method of Operation:**

An access card or other credential is presented to the customer supplied access control reader mounted inside the casework. If entry is authorized, the top mounted indicator LEDs will light as a green arrow pointing in the direction authorized and a chime will sound indicating to the user that they may pass. Unauthorized access attempts and tailgaters are singled out by local visual/audible alarms.

**Optical Detection:**

Industrial duty infrared photoelectric beams (36) linked to Primary Input/output Board - 32-bit microprocessor with optional on board wireless LAN connectivity.

**Throughput:**

One person per second. (Subject to access control system outputs)

**Tailgate Detection:**

The system recognizes patterns of movement through the lane to differentiate between a person pushing or pulling an item and a person attempting to piggy back on a valid entry. Beam scanning algorithmic pattern detection allows valid users of the lane to be within ¼ inch.

**Sound Card:**

The Sound Card emits 4 different tones via an 8 ohm speaker to indicate lane status – i.e.; valid transaction, invalid card, unauthorized access attempt, or tailgate attempt. Digitally controlled, the Sound Card allows for volume adjustment on-board pedestal or via the optional touch screen controller.

**Reader Integration:**

Mounting for proximity card readers are located at both ends, immediately under the LED array. Bar Code readers, Swipe readers, biometric readers, or other access control systems can be integrated.

## PONB-48 Pure Optical No Barrier

- Power:** 240w 24VDC 10A power supply is provided by manufacturer for each set of up to 4 lanes. A dedicated 120V 15A circuit should be provided at each location.
- Status Lights:** LED arrays are fitted into the pedestal tops, one for each direction, to visually assist the user when passing through the lane. Can also be front mounted if required.
- Crawl Under Detection:** Beams detect barrier arm crawl-under attempts, as low as ten inches from the floor, and will trigger a visible and audible alarm and appropriate trigger signal to the access control system.
- Crawl Over Detection:** Utilizes load cell technology to detect an intruder attempting to walk or crawl along the length of the pedestal top to gain entry into the building.
- Bi-directional Card Stacking:** For increased throughput, the system is capable of receiving up to 50 authorized access card credits. If all of the access credits are not used or after 5 seconds of inactivity, the system will reset and secure the lane. Card stacking is active in both directions simultaneously.
- Warranty:** Three (3) year return-to-factory warranty on all electrical components.

### Dimensions:

Pure Optical No Barrier	TYPE	ADA	Standard	With Flat Ends
LANE WIDTH	Inches	36	28	28
PEDESTAL LENGTH	Inches	48	48	42
PEDESTAL HEIGHT	Inches	38	38	38
PEDESTAL WIDTH	Inches	7	7	7

Dimensions are expressed in inches. The colors presented herein are merely illustrative. Turnstiles.us, Inc. reserves the right to change product specifications without prior notice. Prices and specifications are subject to change without notice. Not responsible for typographical errors.